

LOADPRO MCB

Main Features

- Meets the requirements of EN 60898-1
- 6kA rated breaking capacity
- Contact position indicator
- Operational voltage is 240V
- Frequency 50/60 Hz

CATALOGUE NUMBERS

| Current Rating (A) | B Type Product Code | C Type Product Code |
|--------------------|---------------------|---------------------|
| 6 | CS1PB06A | CS1PC06A |
| 10 | CS1PB10A | CS1PC10A |
| 16 | CS1PB16A | CS1PC16A |
| 20 | CS1PB20A | CS1PC20A |
| 32 | CS1PB32A | CS1PC32A |
| 40 | CS1PB40A | CS1PC40A |
| 50 | CS1PB50A | CS1PC50A |
| 63 | CS1PB63A | CS1PC63A |



MCB Accessories

| Description | Product Code |
|----------------------------------|--------------|
| MCB Dolly locking device | KDL |
| Padlock for dolly locking device | XPL |

Technical data

| | |
|---------------------------------|---|
| Rated voltage | 230V AC |
| Rated insulation voltage | 500V |
| Rated impulse withstand voltage | 600V |
| Energy limiting class | 3 |
| Breaking capacity | 6 kA |
| Energy Limiting Class | 3 |
| Rated frequency | 50/60Hz |
| Characteristic | B,C |
| Terminals | 16mm ² up to 25A 25mm ² 32A to 63A |
| Protection degree | IP20 |
| Ambient temperature | -5°C ... +40°C |

