

LOADPRO RCBO TYPE A

Main Features

- Meets the requirements of EN 61009-1
- 6kA rated breaking capacity
- Contact position indicator
- RCBO Type: A
- Maximum cable termination is 16mm²
- Operational voltage is 240V
- Frequency 50/60 Hz

CATALOGUE NUMBERS

Current Rating (A)	B Type Product Code	C Type Product Code
6	CR1PSB0630A	CR1PSC0630A
10	CR1PSB1030A	CR1PSC1030A
16	CR1PSB1630A	CR1PSC1630A
20	CR1PSB2030A	CR1PSC2030A
32	CR1PSB3230A	CR1PSC3230A
40	CR1PSB4030A	CR1PSC4030A
50	CR1PSB5030A	CR1PSC5030A



MCB Accessories

Description	Product Code
MCB Dolly locking device	KDL
Padlock for dolly locking device	XPL

Technical data

Rated voltage	240V AC
Breaking capacity	6 kA
Residual current off time	≤0.1s
Rated frequency	50/60Hz
Breaking capacity	6 kA
Rated tripping current	30mA
Residual current off time	≤0.1s
Characteristic	B,C
Energy Limiting Class	3
Terminals	1-16mm ² , max. 2 Nm
Mechanical endurance	10000
Electrical endurance	4000
Ambient temperature	-25°C ... +40°C

