

## LOADLIMITER 63 RCBO DOUBLE MODULE

### Main Features

- Meets the requirements of EN 61009
- Single Pole and Switch Neutral configuration
- Double module: Type A
- 10kA Rated breaking capacity
- Rated voltage 230V and rated frequency 50Hz
- Maximum cable termination capacity is 35mm<sup>2</sup> for incoming and outgoing terminals
- Maximum terminal torque is 3Nm

### CATALOGUE NUMBERS

Current Rating (A)	Sensitivity (mA)	B Type Product Code	C Type Product Code
6	30	KR2PB0630A	KR2PC0630A
10	30	KR2PB1030A	KR2PC1030A
16	30	KR2PB1630A	KR2PC1630A
20	30	KR2PB2030A	KR2PC2030A
32	30	KR2PB3230A	KR2PC3230A
40	30	KR2PB4030A	KR2PC4030A

NOTE: Please be advised that some varieties of double module RCBOs have a minimum order quantity. Please contact Customer Services to confirm before ordering.



### Technical data

Rated voltage	230 V AC
Minimal supply voltage	90V
Rated frequency	50/60Hz
Rated short-circuit capacity	10kA
Back-up fuse	100A gG
Tripping characteristics	B,C
Peak withstand current	250A
Rated residual making and breaking capacity	10000A
Resistance to vibrations acc. to IEC 60068-2-7	5g (10,60 & 500Hz)

