

## LOADSWITCH 315/400A HOUSED FUSE COMBINATION UNIT

Catalogue Number	HBK3P315N	HBL3P400N	HBL4P400
<b>Main Features</b>			
Relevant Standards	EN 60947-3		
Ingress Protection	IP4X		
Current Rating	315A	400A	400A
Poles	TP&N	TP&N	4P
Short Circuit Capacity (Fused)	80kA rms		
Rated voltage	415V AC		
Utilisation Category	AC23A		
Mechanical Endurance	8,000	5,000	5,000
kW at 415V AC	160	230	230
<b>Construction</b>			
Thickness	1.2/1.6mm		
Material of Enclosure	Zinc coated steel sheet to BS EN 10152		
Paint Finish	Polyester powder coat to RAL7035		
Overall Dimensions (HxWxD) (Incl. Handle)(mm)	738 x 420 x 325		
Weight	21kg		
<b>Installation</b>			
Mounting	4 x keyhole slots		
Gland Plates	Top and bottom removable blank plates		
Gland Plate Knockouts	None		
Earth Stud (Supplied)	M8		
<b>Cables</b>			
Terminal Type	M10 inserted		
Maximum Cable*	4C 185mm <sup>2</sup>	4C 300mm <sup>2</sup> **	4C 185mm <sup>2</sup> **
Maximum Cable Lug Palm Width (mm)	35	50	50
Lug Fixing Screws Supplied	Yes		
<b>Fuses</b>			
Fuse type	BS88 ref B1/B2/B3/B4 Fuse Links Centre Tag Type		
Fuse equivalents	Lawson/GEC – TF/TKF/TMF; Bussmann – CD/DD/ED		
Fuses Supplied	No		
<b>Accessories Cat No.s</b>			
Solid Isolator Link (1 required per phase)	HLL400		
Cable Spreader Box	HB400CSB		
Cable Spreader Box Height (mm)	210		
Castell*** lock mounting kit	SCLK		

\*These figures are for guidance only.

\*\* 240mm<sup>2</sup> with terminal barriers fitted.

\*\*\*Castell is a trademark of Castell Safety International Limited

NOTE: Standard symbol DS1, special symbols are available direct from Castell\*. Quote reference: Castell FS2 – Spigot 9.5mm square x 22.5mm, 65° anti-clockwise to trap key.



## LOADSWITCH 315/400A HOUSED FUSE COMBINATION UNIT

