

LOADLIMITER 63M MODULAR CONTACTOR

Main Features

- Meets the requirements of EN 61095
- DIN-rail mountable

CATALOGUE NUMBERS

Current Rating (A)	No. of Poles	Contact Status	Product Code
20	2	Normally Open	LMC/2/20/2/1
20	2	Normally Closed	LMC/2/20/2/2
25	4	Normally Open	LMC/4/25/2/8
25	4	Normally Closed	LMC/4/25/2/9
40	4	Normally Open	LMC/4/40/2/8
63	4	Normally Open	LMC/4/63/2/8
Ventilation Kit	9mm wide	-	LLMV *

*Ventilation module must be fitted between alternate pairs of contactors to prevent overheating.



Technical data

Rated voltage	2P - 250V AC; 4p - 400V AC
Rated insulation voltage	440V
Rated frequency	50/60Hz
Maximum power	AC1 220/230VAC: 20A 4.5kW, 25A 16kW AC-1/AC-7a 380/400VAC: 63A 40kW AC-3/AC-7b 380/400VAC: 25A 15kW, 4kW
Terminal capacity	20/25A; 1.5-6mm ² : 40/63A; 6-35mm ²
Coil terminal capacity	0.75-2.5mm ²
Terminal tightening	0.8-3.5Nm
Electrical endurance	≥100,000
Mechanical endurance	≥5,000,000
Degree of protection	IP20
Operating temperature	-5°C ... +60°C

