

## LOADLIMITER 63M TYPE A RCCB

### Main Features

- Meets the requirements of EN 61008-1
- 240V and 415V rated
- Frequency 50 / 60Hz
- Type A
- 100A Time delay versions available
- Maximum cable termination is 35mm<sup>2</sup>

### CATALOGUE NUMBERS

Current Rating (A)	Sensitivity (mA)	Product Code
<b>Double-pole RCCBs</b>		
40	30	ME40/30/2A
40	100	ME40/100/2A
63	30	ME63/30/2A
63	100	ME63/100/2A
63	300	ME63/300/2A
80	30	ME80/30/2A
100	30	ME100/30/2A
100	100	ME100/100/2A
100 Time delay	100	MES100/100/2A

### Four-pole RCCBs

40	30	ME40/30/4A
40	100	ME40/100/4A
40	300	ME40/300/4A
63	30	ME63/30/4A
63	100	ME63/100/4A
63	300	ME63/300/4A
100	30	ME100/30/4A
100	100	ME100/100/4A
100	300	ME100/300/4A
100 Time delay	100	MES100/100/4A

### Technical data

Rated voltage	2P - 240V AC; 4p - 415V AC
Rated frequency	50/60Hz
Rated short-circuit capacity	10kA
Rated impulse withstand	4kV
Rated residual non-operating current	0.5 x In
Residual current off time	≤0.1s
Terminal capacity	35mm <sup>2</sup>
Degree of protection	IP20
Operating temperature	-25°C ... +40°C

