

QUICK2FIT MD2 DUAL CHANNEL DIN METER

Main Features

- Reduced installation time with simple plug in connectors
- 2 x separate 3 phase or 6 x single phase 300mV inputs from Quick2Fit CTs (or -/5A CT input with TAS-SCTEWA5A module)
- 4 module DIN-rail mounted
- High definition white backlit LCD screen
- Energy pulse LED
- True RMS measurement
- Single phase or three phase network compatible
- 2 x pulsed output and Modbus as standard
- Independently programmable CT ratios (Load 1 & Load 2)
- Programmable voltage ratio
- Simple programming and operation
- Voltage out connector for daisy chaining up to 32 meters from one supply



CATALOGUE NUMBER

Quick2Fit DIN rail dual channel MF meter c/w Pulse & Modbus MD2

Technical data

GENERAL

Wiring input	3Ø - 4 wire / 1Ø - 2 wire
Rated input voltage	60 - 300V AC (L-N); 104 - 520V AC (L-L)
Frequency range	45 - 65Hz
CT primary	5A - 10,000A
CT secondary	330mV
PT primary	100V - 10kV
PT secondary	100 - 500V AC (L-L)
Auxiliary	Self supplied
Voltage rated burden	191VA (L1 - supply), <0.2VA (L2 & L3)
Operating temperature	-10...+55 °C
Storage temperature	-20...+70 °C
Humidity	0...85% non-condensing
Weight	200g
Pulse output	5-24V DC / Vmax= 27V DC / Imax = 100mA/ 2 x \square (CT1/CT2) (6 X 1Ø: \square ₁ =CH1+CH2+CH3, \square ₂ =CH4+CH5+CH6)
Installation category	III

ACCURACY

Voltage V L-N	± 0.5% of full scale
Voltage V L-L	± 0.5% of full scale
Current	± 0.5% of full scale
Frequency	± 0.1% (L-N >20V / L-L >35V)
Active power	± 1% of full scale
Reactive power	± 1% of full scale
Apparent power	± 1% of full scale
Active energy	Class 1 (IEC/EN62053-21)
Reactive energy	Class 2 (IEC/EN62053-22)
MAX / MIN (Active power/	
Reactive power/Apparent power)	± 1% of full scale
Power factor	± 0.01
THD	3%

QUICK2FIT MD2 DUAL CHANNEL DIN METER

RESOLUTION

PT Ratio x CT Ratio	kWh	
< 15	0.01k	0.001k
< 150	0.1k	0.01k
< 1500	1k	0.1k
< 15000	0.01M	1k
≥ 150000	0.1M	0.01M

1. V / A / W / VA /VAr = auto (1/k/M)
2. PF = 0.01

SERIAL COMMUNICATION

Standard & Protocol	RS485 & Modbus RTU
Communication address	1 to 255
Transmission mode	Half duplex
Data types	Float & Integer
Transmission distance	500m (max)
Transmission speed	300,600, 1200, 2400, 4800, 9600, 19200 bps
Parity	None, Odd, Even
Stop bits	1 or 2
Response time	100mS (Max and independent of baud rate)

Modbus Register Addresses List available for download at www.dormansmithswitchgear.com, alternatively contact Customer service.

